

AISLADORES POLIMERICOS



TIPO AISLADOR	NORMA	CLASE	CARGA MECANICA NOMINAL (kN)	RESISTENCIA A LA FLEXIÓN (kN)	TENSIÓN MÁXIMA DE OPERACIÓN (kV)	DISTANCIA DE FUGA (mm)
Retención (Anclaje)	ANSI C29.13	Clase DS-15	44,5	-	15	355
	ANSI C29.13	Clase DS-28	44,5	-	25	560
	ANSI C29.13	Clase DS-35	44,5	-	35	740
	ANSI C29.13	Clase DS-46	44,5	-	35	900
Line Post (Pilar)	IEC 61952	12,5 - 15 - 355	-	12,5	15	355
	IEC 61952	12,5 - 25 - 560	-	12,5	25	560
	IEC 61952	12,5 - 35 - 740	-	12,5	35	740
Pin (Perno Rígido)	IEC 61109	13 - 15 - 300	-	13	15	300
	IEC 61109	13 - 25 - 350	-	13	25	350
	IEC 61109	13 - 25 - 550	-	13	25	550
	IEC 61109	13 - 36 - 530	-	13	36	530
	IEC 61109	13 - 36 - 700	-	13	36	700



CORPORACION ELECTRICA LIMA

TELEFAX : 540 1879 99809 9460

RPM # 630911 #630908 99809 6092

[Http://www.corporacionelectricalima.com](http://www.corporacionelectricalima.com)

contacto@corporacionelectricalima.com

